

## Up to 14.5 SEER, 12 EER PACKAGE HEAT PUMP, 2.5 to 5 TONS 208/230-3-60 & 460-3-60 Three Phase

### REFRIGERATION CIRCUIT

- Environmentally sound R-410A refrigerant
- Copper tube/aluminum fin condenser and evaporator coils
- Scroll compressor standard on all models
- Short-cycling protection for the compressor is built into the defrost control board
- Dehumidification mode (airflow reduction) on all models

### EASY TO INSTALL AND SERVICE

- Installs easily on a rooftop or at ground level
- Easy three-panel accessibility for maintenance and installation
- Easily converts to down discharge applications
- Combination electric heating and cooling

### BUILT TO LAST

- Direct Drive high efficiency ECM indoor blower motor on all models
- Vertical condenser fan discharge
- Full perimeter steel base rails
- High and low pressure switches provide added reliability for the compressor
- Three phase models have 2" spacing wire grilles

### LIMITED WARRANTY\*

3 Phase PHD4 "E" Models

- 5 year compressor limited warranty
- 1 year parts limited warranty

\* See warranty certificate for complete details and restrictions.



As an Energy Star® Partner, International Comfort Products, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

UNIT PERFORMANCE DATA								
Model Number	COOLING			HEATING		Unit Dimensions Height x Width x Depth in (mm)	Operating Weight lbs (kg)	Notes
	Capacity BTU/h	SEER	EER	Capacity BTU/h	HSPF			
<b>208/230-3-60</b>								
PHD430000H000E	28,600	14.2	12.0	29,600	8.0	44-1/8 x 48-3/16 x 32-5/8 (1121 x 1224 x 829)	340 (154)	
PHD436000H000E	35,800	14.5	12.0	35,800	8.0	44-3/4 x 48-3/16 x 44-3/16 (1137 x 1224 x 1122)	418 (190)	
PHD442000H000E	40,500	14.5	12.0	41,500	8.0	48-3/4 x 48-3/16 x 44-3/16 (1238 x 1224 x 1122)	464 (210)	
PHD448000H000E	46,500	14.5	12.0	45,500	8.0	48-3/4 x 48-3/16 x 44-3/16 (1238 x 1224 x 1122)	452 (205)	
PHD460000H000E	57,000	14.5	12.0	59,000	8.0	54-3/4 x 48-3/16 x 44-3/16 (1391 x 1224 x 1122)	506 (230)	
<b>460-3-60</b>								
PHD436000L000E	35,800	14.5	12.0	35,800	8.0	44-3/4 x 48-3/16 x 44-3/16 (1137 x 1224 x 1122)	432 (196)	
PHD442000L000E	40,500	14.5	12.0	41,500	8.0	48-3/4 x 48-3/16 x 44-3/16 (1238 x 1224 x 1122)	476 (216)	
PHD448000L000E	46,500	14.5	12.0	45,500	8.0	48-3/4 x 48-3/16 x 44-3/16 (1238 x 1224 x 1122)	466 (211)	
PHD460000L000E	57,000	14.5	12.0	59,000	8.0	54-3/4 x 48-3/16 x 44-3/16 (1391 x 1224 x 1122)	520 (236)	